

F-Matic Cinnamon 9,000 Metered Spray

Safety Data Sheet

1 Identification

Product Name: F-MATIC Cinnamon 9,000 Metered Spray

Application of the substance /the mixture Air Freshener

Manufacturer/Supplier:

F-Matic

299 South Millpond Rd.

Lehi, UT 84043 (801) 768-2000

Information department: Product safety department Emergency telephone number: (800) 824-9994

2Hazard(s) identification

Classification of the substance or mixture



GHS02Flame

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness. STOTSE 3

Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms







GHS02

GHS04

GHS07

Signal word Danger

Hazard-determining components of labeling:

acetone

Eugenol

Hazard statements

Extremelyflammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

May cause an allergic skin reaction.

(Contd. on page 2)

Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: F-MATIC Cinnamon 9,000 Metered Spray

(Contd. of page 1)

May cause drowsiness or dizziness.

Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust/fume/gas/mist/vapors/spray

Washthoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves /eye protection /face protection.

If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Call a poison center/doctor ifyou feel unwell.

Specific treatment (see on this label).

Ifskin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0-4)



Health = 2Fire = 4

Reactivity =

HMIS-ratings (scale 0-4)



Health = 2 Fire = 4

Reactivity =

1

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous	components:	
67-64-1	acetone	>50-≤100%
75-28-5	isobutane	>10-≤25%
74-98-6	propane	>2.5-≤10%

(Contd. on page 3)

Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: F-MATIC Cinnamon 9,000 Metered Spray

	(Contd. of page 2)
106-97-8 butane	≤2.5%
Fragrance Trade Secret (791)	≤2.5%

4First-aid measures

- Description offirst aid measures
- After inhalation:
- Supplyfresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Rinse opened eyefor several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
- Nofurther relevant information available.

5Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:
- Usefire-extinguishing media appropriate for surrounding materials. Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Special hazards arising from the substance or mixture Nofurther relevant information available.
- Advice for firefighters
- Protective equipment: No special measures required.

6Accidental release measures

- Personal precautions, protective equipment and emergency procedures
- Wearprotective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

67-64-1 acetone 75-28-5 isobutane	200ppm
75-28-5 isobutane	5 5 0 O d
75 26 5 Bootaine	5500*ppm
74-98-6 propane	5500*ppm
106-97-8 butane	5500*ppm
142-90-5 dodecyl methacrylate	6.9ppm
110-91-8 morpholine	30ppm

(Contd. on page 4)

Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: F-MATIC Cinnamon 9,000 Metered Spray

91-64-5	Coumarin	(Contd. of page 0.88 mg
120-51-4	Benzylbenzoate	5.7 mg/s
100-51-6	Benzyl alcohol	30ppm
PAC-2:		
67-64-1	acetone	3200*ppn
75-28-5	isobutane	17000**p
74-98-6	propane	17000** p
106-97-8	butane	17000**p
142-90-5	dodecyl methacrylate	76ppm
110-91-8	morpholine	1,300ppm
91-64-5	Coumarin	9.7 mg/m³
120-51-4	Benzylbenzoate	63 mg/m³
100-51-6	Benzylalcohol	52ppm
PAC-3:		
67-64-1	acetone	5700*ppm
75-28-5	isobutane	53000*** p
74-98-6	propane	33000*** p
106-97-8	butane	53000*** p
142-90-5	dodecyl methacrylate	460ppm
110-91-8	morpholine	8000** ppn
91-64-5	Coumarin	$58\mathrm{mg/m^3}$
120-51-4	Benzylbenzoate	$380\mathrm{mg/m^3}$
100-51-6	Benzyl alcohol	740ppm

7Handling and storage

- Handling
- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires:
- Do not spray on a naked flame or any incandescent material.
- Keep ignition sources away Do not smoke.
- Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurized containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)

Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: F-MATIC Cinnamon 9,000 Metered Spray

(Contd. of page 4)

Control parameters

Components with limit values that require monitoring at the workplace:

Thefollowing constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

Atui	Attnis time, the remaining constituent has no known exposure limits.			
67-6	67-64-1 acetone			
PEL	PEL Long-term value: 2400 mg/m³, 1000 ppm			
REL	Long-term value: 590 mg/m³, 250 ppm			
TL	Short-term value: 1187 mg/m³, 500 ppm			
V	Long-term value: 594 mg/m³, 250 ppm			
	BEI			
75-2	8-5 isobutane			
TL	Short-term value: 2370 mg/m³, 1000 ppm			
V	(EX)			
74-9	8-6propane			
PEL	Long-term value: 1800 mg/m³, 1000 ppm			
REL	Long-term value: 1800 mg/m³, 1000 ppm			
TL	refer to Appendix F inTLVs&BEIs book; D, EX			
106-	97-8 butane			
REL	Long-term value: 1900 mg/m³, 800 ppm			
TL	Short-term value: 2370 mg/m³, 1000 ppm			
V	V (EX)			
Ingre	Ingredients with biological limit values:			
67-6	67-64-1 acetone			
BEI	$50\mathrm{mg/L}$			
	Medium: urine			
	Time: end of shift			
	Parameter: Acetone (nonspecific)			

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

ininediately remove an sofied and contaminated clothing

Washhands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 6)

Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: F-MATIC Cinnamon 9,000 Metered Spray

(Contd. of page 5)

(Contd. on page 7)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Safety glasses



Tightly sealed goggles

9Physical and chemical properties

Information on basic physical and ch	emical properties
General Information	
Appearance:	
Form:	Aerosol
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-94.7 °C (-138.5 °F)
Boiling point/Boiling range:	-44 °C (-47.2 °F)
Flash point:	< 0 °C (<32 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	460 °C (860 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	1.8 Vol %
Upper:	13 Vol %
·Vapor pressure at 20 °C (68 °F):	3,000 hPa (2,250.2 mm Hg)
Density:	Not determined.
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not applicable.
Solubility in /Miscibility with	
Water:	Not miscible or difficult to mix.

Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: F-MATIC Cinnamon 9,000 Metered Spray

		(Contd. of pag
Partition coefficient (n-octano	l/water): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	83.8 %	
VOC content:	26.05 %	
	$16.0\mathrm{g/l}\ / 0.13\mathrm{lb/gal}$	
Solids content:	3.8 %	
Other information	Nofurther relevant information available.	

10Stability and reactivity

Reactivity No further relevant information available.

- Chemical stability
- Thermal decomposition /conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects

Acute toxicity:

-LD/LC50	LD/LC50 values that are relevant for classification:		
67-64-1	67-64-1 acetone		
		5,800 mg/kg (rat)	
Dermal	LD50	20,000 mg/kg (rabbit)	

Primary irritant effect:

on the skin: No irritant effect.

on the eye: Irritating effect.

Sensitization: Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Carcinogenic categories

IARC (Inte	IARC (International Agency for Research on Cancer)		
97-53-0	Eugenol	3	
110-91-8	morpholine	3	
91-64-5	Coumarin	3	
NTP (Nati	NTP (National Toxicology Program)		
None of th	ne ingredients is listed.		
	(Contd. on pa	ge 8)	

Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: F-MATIC Cinnamon 9,000 Metered Spray

(Contd. of page 7)

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12Ecological information

- ·Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13Disposal considerations

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

14 Transport information

·UN-Number		
DOT, IMDG, IATA	UN1950	
UNproper shipping name		
DOT	Aerosols, flammable	
IMDG	AEROSOLS	
IATA	AEROSOLS, flammable	
Transport hazard class(es)		
DOT		
Class	2.1	
Class Label	2.1 2.1	
IMDG, IATA		
·Class	2.1	
Label	2.1	
Packing group		
DOT, IMDG, IATA	not regulated	

Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: F-MATIC Cinnamon 9,000 Metered Spray

Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Gases
Danger code (Kemler):	-
EMS Number:	F-D,S-U
Stowage Code	SW22For AEROSOLS with a maximum capacity of 1 litre: Catego A.For AEROSOLS with a capacity above 1 litre: Category B. F
	WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre
	Segregation as for class 9. Stow "separated from" class 1 except f
	division 1.4. For AEROSOLS with a capacity above 1 litro
	Segregation as for the appropriate subdivision of class 2. F
	WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	Onpassenger aircraft/rail: 75 kg
Quantity limitations	Onpassenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
Quantity limitations -IMDG	
·IMDG	On cargo aircraft only: 150 kg
IMDG Limited quantities (LQ)	On cargo aircraft only: 150 kg 1L

15Regulatory information

·Safety, health and environmental regulations/legislation specific for the substance or mixture ·Sara

Sara			
Section 355	Section 355 (extremely hazardous substances):		
None of the	None of the ingredients is listed.		
Section 313	Section 313 (Specific toxic chemical listings):		
None of the	None of the ingredients is listed.		
TSCA (Toxic	Substances Control Act):		
67-64-1	acetone		
75-28-5	isobutane		
74-98-6	propane		
106-97-8	butane		
25265-71-8	Dipropylene glycol (isomer unspecified)		
97-53-0	Eugenol		
142-90-5	dodecyl methacrylate		
110-91-8	morpholine		
91-64-5	Coumarin		
	(Contd. on page 10)		

Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: F-MATIC Cinnamon 9,000 Metered Spray

		(Contd. of page 9)
104-55-2	cinnamaldehyde	
97-54-1	Isoeugenol	
120-51-4	Benzyl benzoate	
104-54-1	Cinnamyl alcohol	
100-51-6	Benzyl alcohol	
106-24-1	Geraniol	
TSCA new (21st Century Act) (Substances not listed)		
Fragrance Trade Secret (791)		
Proposition 65		
Chemicals known to cause cancer:		
None of the ingredients is listed.		
Chemicals known to cause reproductive toxicity for females:		
None of the ingredients is listed.		
Chemicals known to cause reproductive toxicity for males:		
None of the	ingredients is listed.	
Chemicals known to cause developmental toxicity:		
None of the ingredients is listed.		
Carcinogenic	categories	
EPA (Environmental Protection Agency)		
67-64-1 acetone		

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms







GHS07

GHS02

GHS04

Signal word Danger

8

Hazard-determining components of labeling:

acetone

Eugenol

Hazard statements

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

(Contd. on page 11)

Printing date 06/04/2019 Reviewed on 06/04/2019

Trade name: F-MATIC Cinnamon 9,000 Metered Spray

(Contd. of page 10)

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust/fume/gas/mist/vapors/spray

Washthoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves /eye protection /face protection.

If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Call a poison center/doctor ifyou feel unwell.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Date of preparation / last revision 06/04/2019 / 17

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT:Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit
Flam. Aerosol 1: Aerosols – Category 1
Press. Gas: Gases under pressure – Compressed gas
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1
STOTSE 3: Specific target organ toxicity (single exposure) – Category 3

*Data compared to the previous version altered.

US