

**1 Identification**

Product Name: F-Matic Ocean Mist 9,000 Metered Spray

Application of the substance /the mixture Air Freshener

Manufacturer/Supplier:

F-Matic  
 299 South Millpond Rd.  
 Lehi, UT 84043

Information department: Product safety department

Emergency telephone number: (800) 824-9994

**2 Hazard(s) identification**

Classification of the substance or mixture



GHS02 Flame

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOTSE 3 H336 May cause drowsiness or dizziness.

Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS02

GHS04

GHS07

Signal word Danger

Hazard-determining components of labeling:

acetone

p-t-Butyl-alpha-methylhydrocinnamic aldehyde

alpha-Hexylcinnamaldehyde

Hazard statements

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

## Safety Data Sheet

Printing date 06/04/2019

Reviewed on 06/04/2019

Trade name: F-Matic Ocean Mist 9,000 Metered Spray

(Contd. of page 1)

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

## Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves / eye protection / face protection.

If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

## Classification system:

NFPA ratings (scale 0-4)



Health = 1

Fire = 4

Reactivity = 1

HMIS-ratings (scale 0-4)



Health = 1

Fire = 4

Reactivity = 1

## Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

## 3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
67-64-1	acetone	>50-≤100%
75-28-5	isobutane	>10-≤25%

(Contd. on page 3)

## Safety Data Sheet

Printing date 06/04/2019

Reviewed on 06/04/2019

Trade name: F-Matic Ocean Mist 9,000 Metered Spray

		(Contd. of page 2)
74-98-6	propane	>2.5-≤10%
106-97-8	butane	≤2.5%
	Fragrance Trade Secret (740)	≤2.5%
80-54-6	p-t-Butyl-alpha-methylhydrocinnamic aldehyde	≥0.1-<1%

#### 4 First-aid measures

Description of first aid measures

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

Information for doctor:

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### 5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents:

Use fire-extinguishing media appropriate for surrounding materials. Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Special hazards arising from the substance or mixture No further relevant information available.

Advice for firefighters

Protective equipment: No special measures required.

#### 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:		
67-64-1	acetone	200 ppm
75-28-5	isobutane	5500* ppm
74-98-6	propane	5500* ppm
106-97-8	butane	5500* ppm

(Contd. on page 4)

## Safety Data Sheet

Printing date 06/04/2019

Reviewed on 06/04/2019

Trade name: F-Matic Ocean Mist 9,000 Metered Spray

(Contd. of page 3)

110-91-8	morpholine	30ppm
142-90-5	dodecyl methacrylate	6.9ppm
100-51-6	Benzyl alcohol	30ppm
PAC-2:		
67-64-1	acetone	3200* ppm
75-28-5	isobutane	17000** ppm
74-98-6	propane	17000** ppm
106-97-8	butane	17000** ppm
110-91-8	morpholine	1,300ppm
142-90-5	dodecyl methacrylate	76ppm
100-51-6	Benzyl alcohol	52ppm
PAC-3:		
67-64-1	acetone	5700* ppm
75-28-5	isobutane	53000*** ppm
74-98-6	propane	33000*** ppm
106-97-8	butane	53000*** ppm
110-91-8	morpholine	8000** ppm
142-90-5	dodecyl methacrylate	460ppm
100-51-6	Benzyl alcohol	740ppm

## 7 Handling and storage

### Handling:

Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

(Contd. on page 5)

## Safety Data Sheet

Printing date 06/04/2019

Reviewed on 06/04/2019

Trade name: F-Matic Ocean Mist 9,000 Metered Spray

(Contd. of page 4)

67-64-1 acetone	
PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TL	Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm
V	Long-term value: 594 mg/m <sup>3</sup> , 250 ppm BEI
75-28-5 isobutane	
TL	Short-term value: 2370 mg/m <sup>3</sup> , 1000 ppm
V	(EX)
74-98-6propane	
PEL	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
TL	refer to Appendix F in TLVs&BEIs book; D, EX
106-97-8 butane	
REL	Long-term value: 1900 mg/m <sup>3</sup> , 800 ppm
TL	Short-term value: 2370 mg/m <sup>3</sup> , 1000 ppm
V	(EX)
Ingredients with biological limit values:	
67-64-1 acetone	
BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

## Safety Data Sheet

Printing date 06/04/2019

Reviewed on 06/04/2019

Trade name: F-Matic Ocean Mist 9,000 Metered Spray

(Contd. of page 5)

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Safety glasses



Tightly sealed goggles

## 9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form:	Aerosol
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.

pH-value: Not determined.

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-11 °C (12.2 °F)

Flash point: &lt; 0 °C (&lt;32 °F)

Flammability (solid, gaseous): Not applicable.

Ignition temperature: 460 °C (860 °F)

Decomposition temperature: Not determined.

Auto igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

Explosion limits:

Lower:	1.8 Vol %
Upper:	13 Vol %

Vapor pressure at 20 °C (68 °F): 3,000 hPa (2,250.2 mm Hg)

Density: Not determined.

Relative density: Not determined.

Vapor density: Not determined.

Evaporation rate: Not applicable.

Solubility in /Miscibility with

Water: Not miscible or difficult to mix.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 7)

## Safety Data Sheet

Printing date 06/04/2019

Reviewed on 06/04/2019

Trade name: F-Matic Ocean Mist 9,000 Metered Spray

(Contd. of page 6)

Solvent content:	
Organic solvents:	83.8 %
VOC content:	26.05 %
	260.5 g/l /2.17 lb/gal
Solids content:	
Other information	4.2 %
	Nofurther relevant information available.

**10 Stability and reactivity**

- Reactivity Nofurther relevant information available.
- Chemical stability
- Thermal decomposition /conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions Nodangerous reactions known.
- Conditions to avoid Nofurther relevant information available.
- Incompatible materials: Nofurther relevant information available.
- Hazardous decomposition products: Nodangerous decomposition products known.

**11 Toxicological information**

Information on toxicological effects

·Acute toxicity:

·LD/LC50 values that are relevant for classification:

67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)

·Primary irritant effect:

·on the skin: No irritant effect.

·on the eye: Irritating effect.

·Sensitization: Sensitization possible through skin contact.

·Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

·Carcinogenic categories

·IARC (International Agency for Research on Cancer)

110-91-8 morpholine

3

·NTP (National Toxicology Program)

None of the ingredients is listed.

·OSHA-Ca (Occupational Safety &amp; Health Administration)

None of the ingredients is listed.

**12 Ecological information**

·Toxicity

·Aquatic toxicity: Nofurther relevant information available.

·Persistence and degradability Nofurther relevant information available.

(Contd. on page 8)

## Safety Data Sheet

Printing date 06/04/2019

Reviewed on 06/04/2019

Trade name: F-Matic Ocean Mist 9,000 Metered Spray



(Contd. of page 7)

·Behavior in environmental systems:  
 ·Bioaccumulative potential No further relevant information available.  
 ·Mobility in soil No further relevant information available.  
 ·Results of PBT and vPvB assessment  
 PBT: Not applicable.  
 vPvB: Not applicable.  
 ·Other adverse effects No further relevant information available.

**13 Disposal considerations**

·Uncleaned packagings:  
 ·Recommendation: Disposal must be made according to official regulations.

**14 Transport information**

·UN-Number DOT, IMDG, IATA	UN1950
·UN proper shipping name DOT IMDG IATA	Aerosols, flammable AEROSOLS AEROSOLS, flammable
·Transport hazard class(es) DOT	
	
·Class Label	2.1 2.1
IMDG, IATA	
	
·Class Label	2.1 2.1
·Packing group DOT, IMDG, IATA	not regulated
·Environmental hazards: Marine pollutant:	No
·Special precautions for user ·Danger code (Kemler): ·EMS Number: ·Stowage Code	Warning: Gases - F-D,S-U SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for
·Segregation Code	

(Contd. on page 9)



## Safety Data Sheet

Printing date 06/04/2019

Reviewed on 06/04/2019

Trade name: F-Matic Ocean Mist 9,000 Metered Spray

(Contd. of page 8)

	division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information: DOT	
Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

## 15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture  
Sara

Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
Section 313 (Specific toxic chemical listings):	
None of the ingredients is listed.	
TSCA (Toxic Substances Control Act):	
67-64-1	acetone
75-28-5	isobutane
74-98-6	propane
106-97-8	butane
25265-71-8	Dipropylene glycol (isomer unspecified)
80-54-6	p-t-Butyl-alpha-methylhydrocinnamic aldehyde
118-58-1	benzylsalicylate
101-86-0	alpha-Hexylcinnamaldehyde
110-91-8	morpholine
142-90-5	dodecyl methacrylate
78-70-6	Linalool
106-22-9	dl-Citronellol
127-51-5	alpha-iso-Methylionone
106-24-1	Geraniol
5392-40-5	Citral
100-51-6	Benzyl alcohol
TSCA new (21st Century Act) (Substances not listed)	
Fragrance Trade Secret (740)	

(Contd. on page 10)

## Safety Data Sheet

Printing date 06/04/2019

Reviewed on 06/04/2019

Trade name: F-Matic Ocean Mist 9,000 Metered Aerosol

(Contd. of page 9)

## Proposition 65

Chemicals known to cause cancer:
None of the ingredients is listed.
Chemicals known to cause reproductive toxicity for females:
None of the ingredients is listed.
Chemicals known to cause reproductive toxicity for males:
None of the ingredients is listed.
Chemicals known to cause developmental toxicity:
None of the ingredients is listed.

## Carcinogenic categories

EPA (Environmental Protection Agency)		
67-64-1	acetone	I
TLV (Threshold Limit Value established by ACGIH)		
67-64-1	acetone	A4
110-91-8	morpholine	A4
NIOSH-Ca (National Institute for Occupational Safety and Health)		
None of the ingredients is listed.		

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).  
Hazard pictograms



## Signal word Danger

Hazard-determining components of labeling:  
acetone

p-t-Butyl-alpha-methylhydrocinnamic aldehyde  
alpha-Hexylcinnamaldehyde

## Hazard statements

Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
May cause drowsiness or dizziness.

## Precautionary statements

If medical advice is needed, have product container or label at hand.  
Keep out of reach of children.  
Read label before use.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves /eye protection /face protection.  
If on skin: Wash with plenty of water.

(Contd. on page 11)

## Safety Data Sheet

Printing date 06/04/2019

Reviewed on 06/04/2019

Trade name: F-Matic Ocean Mist 9,000 Metered Spray

(Contd. of page 10)

IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Call a poison center/doctor if you feel unwell.  
 Specific treatment (see on this label).  
 If skin irritation or rash occurs: Get medical advice/attention.  
 If eye irritation persists: Get medical advice/attention.  
 Wash contaminated clothing before reuse.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Store locked up.  
 Protect from sunlight. Store in a well-ventilated place.  
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.  
 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Date of preparation / last revision 06/04/2019 / 12

### Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 BEI: Biological Exposure Limit  
 Flam. Aerosol 1: Aerosols – Category 1  
 Press. Gas: Gases under pressure – Compressed gas  
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A  
 Skin Sens. 1: Skin sensitisation – Category 1  
 STOTSE 3: Specific target organ toxicity (single exposure) – Category 3

### Sources

Additional Information Section 11 and Section 15

“According to IARC Morpholine is not classifiable as to its carcinogenicity to humans (Group 3).

IARC (1989) IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Vol. 47, Some Organic Solvents, Resin Monomers and Related Compounds, Pigments and Occupational Exposures in Paint Manufacture and Painting, Lyon, pp. 199–213”

\*Data compared to the previous version altered.