

F-Matic Mango Micro Mini 3,000 Metered Spray Safety Data Sheet


Reviewed on 05/06/2023

1 Identification

- · Product Name: F-MATIC Mango Micro Mini 3,000 Metered Spray
- Manufacturer article number: MS400
- \cdot Application of the substance / the mixture Air Freshener

• **Manufacturer/Supplier:** F-Matic 299 South Millpond Rd. Lehi, UT 84043 (801) 768-2000

• Emergency Telephone Number: (801) 768-2000





F-MATIC Mango Micro Mini 3,000 Metered Spray

May cause an allergic skin reaction. May cause drowsiness or dizziness. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves / eye protection / face protection. If on skin: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Wash contaminated clothing before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 2Fire = 4*Reactivity* = 1· HMIS-ratings (scale 0 - 4) HEALTH 2 Health = 2FIRE 4 Fire = 4**REACTIVITY** 1 Reactivity = 1· Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

· Dangero	us components:	
67-64-1	acetone	>50-≤100%
74-98-6	propane	>10-≤25%
106-97-8	butane, pure	>2.5-≤10%

Reviewed on 05/06/2023

F-MATIC Mango Micro Mini 3,000 Metered Spray

Fragrance Trade Secret (742)

≤2.5%

4 First-aid measures

- · Description of first aid measures
- · After inhalation:
- Supply fresh air; remove to outdoors, consult a doctor if conditions worsen.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Consult a doctor if irritation to skin occurs.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Seek medical attention.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- Use fire-extinguishing media appropriate for surrounding materials. Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- **Reference** to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

· PAC-1:		
	acetone	200 ppm
74-98-6	propane	5500* ppm
106-97-8	butane, pure	5500* ppm
5989-27-5	(R)-p-mentha-1,8-diene	15 ppm
100-51-6	Benzyl alcohol	30 ppm
· PAC-2:		
67-64-1	acetone	3200* ppm

F-MATIC Mango Micro Mini 3,000 Metered Spray

74-98-6	propane	17000** ppm
106-97-8	butane, pure	17000** ppm
5989-27-5	(R)-p-mentha-1,8-diene	67 ppm
100-51-6	Benzyl alcohol	30 ppm
• PAC-3:		
	acetone	5700* ppm
67-64-1	acetone propane	5700* ppm 33000*** ppm
67-64-1 74-98-6		5700* ppm 33000*** ppm 53000*** ppm
67-64-1 74-98-6 106-97-8	propane	33000*** ppm

7 Handling and storage

· Handling:

· Precautions for safe handling

Store in a cool dry place. Protect from direct sunlight and prolonged exposure to water. Do not puncture or incinerate container even when empty.

· Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- *Requirements to be met by storerooms and receptacles:* Observe official regulations on storing packagings with pressurized containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

67-64-1 acetone

- PEL Long-term value: 2400 mg/m³, 1000 ppm
- *REL* Long-term value: 590 mg/m³, 250 ppm
- TLV Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm

BEI

74-98-6 propane

PEL Long-term value: 1800 mg/m³, 1000 ppm

(Contd. on page 5)

Reviewed on 05/06/2023

F-MATIC Mango Micro Mini 3,000 Metered Spray

Tele Long term value. 1000 mg/m, 1000 ppm	REL	Long-term value:	1800 mg/m ³ ,	1000 ppm
---	-----	------------------	--------------------------	----------

TLV refer to Appendix F inTLVs&BEIs book; D, EX

106-97-8 butane, pure

REL Long-term value: 1900 mg/m³, 800 ppm

TLV Short-term value: 2370 mg/m³, 1000 ppm (EX)

· Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

• Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

F-MATIC Mango Micro Mini 3,000 Metered Spray

9 Physical and chemical propert	ties
· Information on basic physical and c	chemical properties
· General Information	
· Appearance:	
Form:	Aerosol
Color:	According to product specification
• Odor: • Odor threshold:	Characteristic Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-44 °C (-47.2 °F)
· Flash point:	<0 °C (<32 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	460 °C (860 °F)
• Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.8 Vol %
Upper:	13 Vol %
· Vapor pressure at 20 °C (68 °F):	3,000 hPa (2.300 mm Hg)
· Density:	Not determined.
Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	e r): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	98.1 %
VOC content:	22.06%
	220.6 g/l / 1.84 lb/gal
Solids content:	3.6 %
• Other information	No further relevant information available.

10 Stability and reactivity

• *Reactivity* No further relevant information available.

Reviewed on 05/06/2023

3

3

F-MATIC Mango Micro Mini 3,000 Metered Spray

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

67-64-1 acetone

Oral LD50 5,800 mg/kg (rat)

Dermal LD50 20,000 mg/kg (rabbit)

• Primary irritant effect:

• on the skin: No irritant effect.

• on the eye: Irritating effect.

• Sensitization: Sensitization possible through skin contact.

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

5989-27-5 (R)-p-mentha-1,8-diene

91-64-5 Coumarin

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

F-MATIC Mango Micro Mini 3,000 Metered Spray

13 Disposal considerations

Uncleaned packaging:
Recommendation: Disposal must be made according to official regulations.

Transport information	
· UN-Number · DOT, IMDG, IATA	UN1950
· UN proper shipping name · DOT · IMDG	Aerosols, flammable AEROSOLS
· IATA	AEROSOLS, flammable
· Transport hazard class(es)	
· DOT	
· Class	2.1
· Label	2.1
· Class · Label	2.1 2.1
· Packing group · DOT, IMDG, IATA	not regulated
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user	Warning: Gases
• Hazard identification number (Kemler c	
· EMS Number: · Stowage Code	F-D,S-U SW22 For AEROSOLS with a maximum capacity of 1 litre Category A. For AEROSOLS with a capacity above 1 litre Category B. For WASTE AEROSOLS: Category C, Clear of livin quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.

Reviewed on 05/06/2023

F-MATIC Mango Micro Mini 3,000 Metered Spray

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 75 kg
	On cargo aircraft only: 150 kg
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxi	c Substances Control Act):	
67-64-1	acetone	ACTIVE
74-98-6	propane	ACTIVE
106-97-8	butane, pure	ACTIVE
5989-27-5	(R)-p-mentha-1,8-diene	ACTIVE
100-51-6	Benzyl alcohol	ACTIVE
78-70-6	Linalool	ACTIVE
5392-40-5	Citral	ACTIVE
· Hazardous A	Air Pollutants	

None of the ingredients is listed.

· Chemicals known to cause cancer:
None of the ingredients is listed.
· Chemicals known to cause reproductive toxicity for females:

· Proposition 65

Reviewed on 05/06/2023

I

A4

F-MATIC Mango Micro Mini 3,000 Metered Spray

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

67-64-1 acetone

· TLV (Threshold Limit Value)

67-64-1 acetone

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



- · Signal word Danger
- Hazard-determining components of labeling: acetone
- · Hazard statements

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves / eye protection / face protection.

If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

If eve irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Reviewed on 05/06/2023

F-MATIC Mango Micro Mini 3,000 Metered Spray

Protect from sunlight. Store in a well-ventilated place.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision 08/29/2022

· Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Aerosol 1: Aerosols – Category 1 Press. Gas: Gases under pressure - Compressed gas Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 · Sources Additional Information Section 11 and Section 15 "According to IARC Morpholine is not classifiable as to its carcinogenicity to humans (Group 3). IARC (1989) IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Vol. 47, Some Organic Solvents, Resin Monomers and Related Compounds, Pigments and Occupational Exposures in Paint Manufacture and Painting, Lyon, pp. 199–213"